

FLAGRO FV-200RC



Model	FVO-200RC Oil	FVNP-200RC Dual Fuel
Heat Capacity	185,000 BTU/hr	200,000 BTU/hr
Fuel Tank Capacity	23 US Gallons	External
Operating Time	17 hours	N/A
Fuel Consumption	1.32 GPH	Propane 2.18 GPH Natural 200 CFH
Power Requirement	115 Volt / 15 Amp	115 Volt / 15 Amp
Heat Exchanger	16 Gauge Fully Welded 304 Stainless Steel	16 Gauge Fully Welded 304 Stainless Steel
Air Flow	2,600 CFM	2,600 CFM
Ignition	Direct Spark Ignition	Direct Spark Ignition
Air Outlet (Standard)	Single 16" Outlet	Single 16" Outlet
(Optional)	Single 12" Outlet	Single 12" Outlet
Return Inlet	Single 16" Inlet	Single 16" Inlet
Wheels	2x 12" Pneumatic Wheels 2x 6" Lockable Casters	2x 12" Pneumatic Wheels 2x 6" Lockable Casters
Approval	cETLus	cETLus
L x W x H	52" x 27" x 48"	52" x 27" x 48"
Weight	350 lbs	300 lbs

DEPENDABLE HEAT WHEREVER YOU NEED IT



Supply is ductable up to 150 feet
 Return is ductable up to 50 feet
 Proven Riello burner technology
 Built in nozzle pre-heater for cold weather start up