## **Rental Chiller Package**

# 350 Ton



## **General System Data**

Fully packaged system, completely assembled, arrives on job site ready for installation in minimal time. Chiller package includes pump matched specifically to range of operation, triple duty valve, piping (includes pump bypass), and in-line Y strainer.

#### **Equipment Features & Options**

- 48' air-ride flatbed trailer
- 50 hp mounted pump package
- Booster pump options
- Pump bypass option
- 6" flanged triple-duty valve
- 6" Y strainer
- Louvered condenser hail guards
- Single point power
- Control transformer
- R-134A refrigerant
- Flow switch with safety interlock
- Voltage 460V / 60Hz / 3Ø
- Louvered condenser hail guards
- Wye delta start
- Service isolation valve
- Low temperature Glycol option


Basic Equipment Data		
Refrigerant	R-134A	
Ambient Range	0-115°	
Chilled Water Setpoint	41-60°	
Refrigerant Circuits	2	
# Compressors	3	
Equipment Insurance Value	\$262,500	


Electrical Data	
Nominal Voltage	460V / 60Hz / 3Ø
Single Point Power Connection (2 per Ø)	16 Series Cam Type
MCA (single point power connection)	678
MCA (single point power connection w/ pump)	737
RLA	628
RLA (with pump)	687

\*\* A separate 115 / 60 / 1, 15 amp customer provided power connection is required to power the evaporator heaters if the potental for freezing conditions exists.




Physical Data		
Length	39'	
Length (with trailer)	48'	
Width	89"	
Width (with trailer)	102"	
Height	96"	
Height (with trailer)	149"	
Operating Weight	22,990 lbs.	





Pump Data		
Flow	840 GPM	
Head	140 FT	
Horsepower	50	
RPM	1800	
Cycle	60	
Phase	3Ø	
FLA	59	



Evaporator Data		
Water Storage	70 Gallons	
Minimum Flow	375 GPM	
Maximum Flow	1374 GPM	
Nominal Flow	840 GPM	
Water Side Max PSI	150 PSI	
Water Connections	6" Flanged	

### Evaporator Water Pressure Drop



