

FLAGRO FV-400RC



Model	FVO-400RC Oil	FVNP-400RC Dual Fuel
Heat Capacity	390,000 BTU/hr	390,000 BTU/hr
Fuel Tank Capacity	42 US Gallons	External
Operating Time	14 hours	N/A
Fuel Consumption	2.75 GPH	Propane 4.25 GPH Natural 390 CFH
Power Requirement	115 Volt / 15 Amp	115 Volt / 15 Amp
Heat Exchanger	16 Gauge Fully Welded 304 Stainless Steel	16 Gauge Fully Welded 304 Stainless Steel
Air Flow	4,000 CFM	4,000 CFM
Ignition	Direct Spark Ignition	Direct Spark Ignition
Air Outlet (Standard)	Single 16" Outlet	Single 16" Outlet
(Optional)	Dual 12" Outlet Single 20" Outlet	Dual 12" Outlet Single 20" Outlet
Return Inlet	Single 16" Inlet	Single 16" Inlet
Wheels	16" Flat Free Wheels	16" Flat Free Wheels
Approval	cETLus	cETLus
L x W x H	70" x 29" x 54"	70" x 29" x 49"
Weight	455 lbs	470 lbs

DEPENDABLE HEAT WHEREVER YOU NEED IT



Supply is ductable up to 150 feet
 Return is ductable up to 50 feet
 Proven Riello burner technology
 Built in nozzle pre-heater for cold weather start up